STATE OF LOUISIANA 04062011

DEPARTMENT OF PUBLIC SAFETY AND CORRECTIONS
OFFICE OF STATE FIRE MARSHAL CODE ENFORCEMENT AND BUILDING SAFETY
8181 INDEPENDENCE BLVD., BATON ROUGE, LA 70806

800-256-5452 225-925-4920 FAX: 225-925-4414

WEB SITE: www.dps.state.la.us/sfm

## LOUISIANA STATE UNIFORM CONSTRUCTION CODE PLAN REVIEW CHECKLIST for structures excluding one-and-two family dwellings

The Office of the State Fire Marshal, Division of Code Enforcement and Building Safety, may review plans of structures excluding one-and-two family dwellings for compliance with the applicable requirements of the Louisiana State Uniform Construction Code (LSUCC) on behalf of parishes or municipalities requesting assistance. Plans and specifications for structures located within a parish or municipality that has requested this office to provide this service will be required to contain additional information for review. The information outlined in this document represents the minimum criteria necessary for this office to determine compliance with the LSUCC. Please note that this list is not comprehensive or all-inclusive and does not address all aspects of every structure.

In order to ensure that the proposed projects can be expeditiously reviewed, the requirements of the LSUCC should be addressed in the documents submitted for review. Applicable codes for commercial structures are as follows:

- 2009 International Building Code (IBC), (excluding Chapters 1, 11, 27, and 29);
- 2009 International Existing Building Code (IEBC), (excluding Chapter 1);
- 2009 International Mechanical Code (IMC):
- 2000 Louisiana State Plumbing Code (LSPC);
- 2009 International Fuel Gas Code (IFGC);
- 2008 National Electric Code (NEC).

Drawings and specifications shall also document compliance with the Louisiana Revised Statutes (LRS, see Fire Marshal's Act on our web site at <a href="www.dps.state.la.us/sfm">www.dps.state.la.us/sfm</a>), the Life Safety Code (NFPA 101) and all promulgated National Fire Codes, the Americans with Disabilities Act Accessibility Guideline (see ADA-AG, under Codes/Rules/Laws on our web site), ANSI A117.1, the Fair Housing Act, the Commercial Building Energy Conservation Code, (L.R.S. 40:1730.41 through 1730.48), the Architects Licensing Law, (L.R.S. 37:155), the Engineers/Land Surveyors Licensing Law (L.R.S. 37:696(B) & LAC 46:LXI. 2701), and the Louisiana State Sanitary Code (LAC Title 51, as may be applicable, see "PLUMBING INFORMATION" below).

The applicable general information contained in this checklist should be clearly identified on the drawings and/or specifications, or provided in the form of an attachment to the contract documents. An attachment is acceptable as long as it is part of the official construction documentation. Failure to provide this information may delay the review of the project or cause it to be rejected for lack of significant information. Additional information and/or drawings are never discouraged and may be necessary to describe complex or unique conditions contained in the project. Where the nature of the work is determined by the local building official to be such that review for compliance with the LSUCC by this office will not be necessary, provide written documentation from the building official to indicate that the required review will be performed by him or her.

As an aid to streamline our architectural plan review process, we ask that you complete this checklist, and attach it to your Plan Review Application. Your help, up front, will facilitate a complete submittal package, shorten our review time, and help us to get your project reviewed and returned sooner. Please verify that each item below is: A. in your submittal, B. correct, and C. is coordinated within the submittal. Provide a check mark adjacent to each item or print "N/A" for items not applicable to this submittal. Thank you for your help, in completing and coordinating the items in this checklist.

# REVIEW APPLICATION, CHECKLIST, FEE & DOCUMENTATION Completed Plan Review Application form; This completed checklist; Check or money order (no cash accepted) for plan review fee, payable to the LA Department of Public Safety. Calculate the required review fee from the Fee Calculation schedule, (visit our website at <a href="www.dps.state.la.us/sfm">www.dps.state.la.us/sfm</a> for a copy of the current fee schedule); One set of drawings (and specifications, if separate) stamped by the architect or civil engineer (Professional of Record, (POR)) preparing the documents when applicable. Drawings shall be legible prints or photocopies, live ink or pencil applied by hand is not acceptable; Provide a brief description of how the building is proposed to be used; Include all existing documentation, if applicable (inspection report(s), equivalency determination letter(s), prior review letter(s), etc.).

# SUGGESTED DRAWINGS AND SPECIFICATIONS FOR **NEW CONSTRUCTION AND ADDITIONS**

COVER		INFORMATION the proposed occupancy classification(s) [IBC Chapter 3];
	-	
	(	Where the building contains multiple occupancy classifications, (not classified as "Accessory" to the main occupancy), indicate whether it's designed as "Separated Occupancies" or "Nonseparated Occupancies" [IBC Section 508];
		Identify any "Accessory Occupancies" [IBC Section 508.2] (other occupancy types less than 10% of the
		main occupancy), and any "Incidental Use Areas" [IBC Table 508.2.5]; Indicate if any "Special Detailed Requirements" based on use and occupancy apply [IBC Chapter 4];
	Identify t	the new construction type (and existing if an addition) [IBC Table 601 (and IEBC Chapter 10 if an addition)];
		the gross square footage of each floor, including any covered open areas that are subject to occupancy. If ect is an addition, identify the existing building area separately [IBC Section 502 and IEBC Section 1002]
	area mo Identify a	Introduction of the allowable height and building area limitations [IBC Chapter 5]. Provide calculations if difications are used [IBC Section 506] any Fire Protection Systems that are to be provided [IBC Chapter 9]: Automatic sprinkler system type and extent; [IBC Section 903] Alternative extinguishing systems; [IBC Section 904] Standpipe system; [IBC Section 905] Portable fire extinguisher size, type and locations; [IBC Section 906]
		Automatic or manual fire alarm system and extent; [IBC Section 907] Other fire protection / suppression systems.
	Design lo	ral Design Data: (May also be indicated on the structural drawings) oads must be included within the construction documents in a manner such that the design loads are clear arts of the structure [IBC Section 1603]. This information is required on ALL projects regardless of the nent of a registered design professional. Loads:
	Indicate	the load values used in the design of the structural components, as applicable: Floor Live load; [IBC Table 1607.1] Roof Live load; [Table 1607.1] Roof (ground) snow load; [IBC Figure 1608.2]
		esign Data:
	Indicate —— —— —— ——	the following: Basic wind speed (3-second gust) for the site location [IBC Figure 1609 or ASCE 7-05 Figure 6-1]; Wind Importance Factor [ASCE Table 6-1]; Occupancy Category [IBC Table 1604.5 or ASCE 7-05 Table 1-1]; Wind Exposure Category [IBC Section 1609.4.3] and applicable governing wind direction; Applicable Internal Pressure Coefficient [ASCE 7-05 Figure 6-5];
		Indicate the design wind pressures in terms of psf used for the design of exterior Component and Cladding materials. the design method used to determine the wind loads (Take note of the specific limitations of each): Conventional Light-Frame Construction provisions of IBC Section 2308, (limited applicability),
		ASCE 7-05 Method 1 - Simplified Method, [ASCE 7-05 Section 6.4] ASCE 7-05 Method 2 - Analytical Method, [ASCE 7-05 Section6.5] ASCE 7-05 Method 3 - Wind Tunnel Procedure, [ASCE 7-05 Section 6.6] AF&PA Wood Frame Construction Manual, (limited applicability), SSTD-10, (limited applicability),
		Other methods or manuals as allowed or required by the code for specific building construction methods.  **Rake Design Data:**
	The follo	owing shall be shown regardless of whether seismic loads govern the design of the lateral-force-resisting of the building: [IBC Sections 1603.1.5 and 1613]  Seismic importance factor [ASCE 7005 Section 11.5];  Occupancy category [IBC Table 1604.5 or ASCE 7-05 Table 1-1];  Mapped spectral response accelerations [IBC Section 1613.5.1];  Site class [IBC Table 1613.5.2 and ASCE 7-05 Chapter 20];

	<ul> <li>Spectral response coefficients [IBC Tables 1613.5.3(1) &amp; 1613.5.3(2)];</li> <li>Seismic design category [IBC Tables 1613.5.6(1) &amp; 1613.5.6(2) – Highest of the two];</li> <li>Identify the basic seismic-force-resisting system(s) [ASCE 7-05 Section 12.2 or Section 12.14.4];</li> <li>Indicate the design base shear [ASCE 7-05 Section 12.8.1 or Section 12.14.8.1];</li> <li>Seismic response coefficient(s) and Response modification factor(s) [ASCE 7-05 Table 12.2-1];</li> <li>Analysis procedure used.[ASCE 7-05 Section 12.6 or Section 12.14]</li> </ul>
	Flood Design Data:
	Indicate the elevation of the lowest floor of the structure and grade elevation [IBC Section 1612]; Identify the flood hazard zone, including feet of water in the zone, where indicated on the FIRM maps; Indicate the Design Flood Elevation of the building [IBC Section 1612.2];
	In <u>ALL</u> Flood Hazard Zones, (A, B, C, D, M, N, P, E, V, and X including modifiers in each designation), the following documentation shall be prepared and sealed by a registered design professional. (Surveyor, Architect, or Civil Engineer)
	Note: FEMA Form 81-31, <i>Elevation Certificate</i> , and FEMA Form 81-65, <i>Floodproofing Certification</i> , recommended for this use in the IBC <i>Commentary</i> are available at <a href="http://www.fema.gov/pdf/nfip/elvcert.pdf">http://www.fema.gov/pdf/nfip/elvcert.pdf</a> and <a href="http://www.fema.gov/plan/prevent/fhm/dl_fpc.shtm">http://www.fema.gov/plan/prevent/fhm/dl_fpc.shtm</a> . Verify acceptance of these forms with the local authority. Also visit the Department of Transportation and Development's Floodplain Management website at <a href="http://floods.dotd.la.gov">http://floods.dotd.la.gov</a> for additional information. For construction in an area <a href="NOT subject to high-velocity wave action">NOT subject to high-velocity wave action</a> (All zones except V);
	Construction documents shall include a statement to indicate that the design will provide for equalization of hydrostatic flood forces in accordance with Section 2.6.2.2 of ASCE 24 if fully enclosed areas below the design flood elevation are provided and do not meet the minimum requirements in Section 2.6.2.1 of ASCE 24. For dry floodproofed nonresidential buildings, construction documents shall include a statement that the dry floodproofing is designed in accordance with ASCE 24.
	For construction located in an area subject to high-velocity wave action (Zones V, VO, VE or V1-30.);
	Construction documents shall indicate the elevation of the lowest horizontal structural member and shall include a statement that the building is designed in accordance with ASCE 24, including that the pile or column foundation and building or structure to be attached thereto is designed to be anchored to resist flotation, collapse and lateral movement due to the effects of wind and flood loads acting simultaneously on all building components, and other load requirements of Chapter 16.
	In designs for required breakaway walls to resist a nominal load of less than 10 psf or more than 20 psf, construction documents shall include a statement that the breakaway wall is designed in accordance with ASCE 24.
SITE P	LAN INFORMATION
	Provide a site plan drawn to a scale indicated on the plan and in accordance with an accurate boundary line survey. Plan should indicate as a minimum:
	Distances of the proposed building from the property lines (when the building stands alone on the property); Distances from "Assumed property lines" (where the building stands with other buildings on the same site.) [IBC Section 503.1.2];
	Identify adjacent buildings and structures and indicate their distances from the subject building. Indicate any potentially hazardous uses (Storage, Industrial occupancies); Adjacent roads, drives, alleys, easements or other public ways;
	Parking areas, including parking layouts, features of accessibility, fence and gate locations;  Design flood elevation, proposed finished floor elevations of the lowest floor and of the lowest finished floor if different, proposed finished grade elevations;
	Flood zone established for the specific site; Location of utilities, (water, gas sewer, electrical, sprinkler water, etc.); Indicate topographic features of the site.
FOUND	DATION PLAN INFORMATION
	Provide a foundation plan drawn to the scale indicated on the plan, dimensioned, and keyed to the floor plan(s). Indicate the design method / manual used for the building foundation / slab. Take note of the specific limitations of each:
	<ul><li>IBC Chapter 18 (may be used in areas not subject to wave action);</li><li>ASCE 24 (Flood resistant design standard);</li></ul>
	Other standards or references as allowed, or required, by the code for specific building foundation types. Identify soil types in the foundation area and the design bearing capacity used for the foundation design. Provide test reports where required [IBC Section 1802]; Plan should indicate as a minimum:

	Foundation types, locations, sizes, depths, shapes, thicknesses, and materials (piers, piles, footings, walls, slabs, etc);
	Specifications for the type, mix ratio, and minimum compressive strength of concrete (where applicable) [IBC Chapter 19];
<u></u>	Locations of air entrained concrete (where required) [IBC Section 1904];
	Reinforcing details, specified strength or grade, placement and sizes [IBC Section 1907]; Imbedded anchoring locations, size and depth [IBC Sections 1911 and 1912];
	Slab layout for recesses, void, and other irregularities;
	Document the elevation of the lowest occupied floor of the structure with respect to grade.
FLOO	R PLAN INFORMATION  Provide floor plan(s) drawn to a scale indicated on the plan and dimensioned. Plan(s) should indicate as a minimum
	Room names and/or uses; Door and Window locations;
	Clearly indicate the type and locations of any required fire resistance rated or smoke rated construction used in the project. (See Fire-Resistance Ratings, Fire Walls, Fire Barriers, Fire Partitions, Smoke Barriers, Smoke Partitions, etc. [IBC Table 601 and Chapter 7]):
	<ul> <li>Building Element protection required by the Construction Type [IBC Table 601]</li> <li>Exterior wall construction [Table 602] including opening protection [IBC Section 705 and Table 705.8]</li> <li>Incidental Accessory Occupancies [IBC Table 508.2]</li> </ul>
	Occupancy Separations (if Separated Occupancies) [IBC Table 508.4]
	Corridors [IBC Section 1018 and Table 1018.1] Exit Enclosures [IBC Sections 1022, 1023, and 1025]
	<ul> <li>Exit Enclosures [IBC Sections 1022, 1023, and 1025]</li> <li>Fire Wall separations [IBC Table 706.4]</li> <li>Fire Area Separations [IBC Table 707.3.9]</li> <li>Shafts and Vertical Openings [IBC Section 708]</li> </ul>
	Fire Area Separations [IBC Table 707.3.9] Shafts and Vertical Openings [IBC Section 708]
	Smoke Barriers and Smoke Partitions [IBC Sections 710 and 711]
	Other conditions that may require protection  Identify the listed tested assemblies, from an approved testing agency, used to achieve the fire resistance rating of
	the proposed construction (UL, ETL, FM, GA, WP, WH, etc.) including joints in the assemblies. [IBC Section 714] Identify key features of the Means of Egress: (Chapter 10)
	Indicate occupant loads for each room in Assembly (A1, A2, A3, A4, and A5) occupancies: [IBC Table 1004.1]
	Indicate stair, corridor, aisle, and doorway widths in all occupancies: [IBC Section 1005] Indicate locations of structural elements, including shear walls used to transfer lateral forces.
SCHE	DULES and DETAILS  Provide sufficient information to identify features indicated in the construction decuments:
	Provide sufficient information to identify features indicated in the construction documents:  Schedules to indicate door / frame and window opening sizes configurations, types, materials, fire resistance ratings and door operating hardware;
	Where the project is located in a wind borne debris region, (basic wind speed = 120 mph or greater), provide details
	specifications and/or schedules to identify the method of opening protection used, and its anchorage to the building. [IBC Sections 1609.1.2 and 1609.2]
	Identify the interior finishes used in each room of the project:
	Walls and Ceilings [IBC Table 803.5] Floors [IBC Section 804]
STRU	CTURAL FRAMING INFORMATION
OTINO	Provide framing plan(s) drawn to a scale indicated on the plan, dimensioned, and keyed to the floor plan(s). Plan(s)
	should indicate as a minimum:
	Floor and roof framing plans (as applicable); Identify structural members - Materials used, Sizes, and spacing;
	Identify the Main Wind Force Resisting System. Provide sufficient detail to demonstrate that the structure has been
	designed to withstand the indicated design loads; Locate lateral bracing, ties, clips, sheathing or other elements and materials used to reinforce or otherwise provide
	stability to the structure and provide continuous path for loads from roof to grade.
	Provide anchorage details. Indicate types, locations, sizes and spacing;  Design loads must be included within the construction documents in a manner such that the design loads are clear
	for all parts of the structure IIBC Section 1603]. (See also COVER SHEET INFORMATION above)

Provide elevations of each side of the building. Plans should indicate as a minimum:  Vertical distance from grade to the average height of the highest roof surface [IBC Sections 502 and 504];  Opening locations;	
For 120 MPH (3 Second Gust) wind zones and above, documents should clearly identify methods used for opening protection;	3
Provide details and specifications to indicate that components and cladding (including the roof deck and roof coverings) are designed and are to be installed to withstand the pressures determined in accordance with ASCE 7 [ASCE 7-05 Sections 6.4.2.2 or 6.5.12.4];  Identify the lateral bracing system.	
BUILDING AND WALL SECTIONS  Wall sections of each bearing wall condition, interior and exterior, to indicate a continuous load path through the	
structure from the roof to the foundation at each condition;	
Drawings should clearly indicate the components required to resist wind forces and to achieve the required "continuous load path" from roof peak to foundation anchorage.	
Provide details and specifications to indicate that components and cladding are designed and installed to withstand	
the pressures determined in accordance with ASCE 7. (See also EXTERIOR ELEVATION INFORMATION above) Identify structural members;	
Identify structural members, Identify materials;	
Provide dimensions;	
Specify anchorage/connector types used and indicate their proposed locations and spacing. (See also STRUCTURAL FRAMING INFORMATION above)	
MECHANICAL INFORMATION	
Provide mechanical drawings to indicate as a minimum:	
Equipment types and locations;  Ductwork and piping sizes, CFM, and locations;	
Mechanical ventilation air balance design calculations;	
Return, supply, exhaust and outdoor air supply in accordance with IMC 403.1, 403.2, 403.2.1, 403.3 and Table 403	3.3
requirements; (see also IBC Section 1017.4 & LSPC 404.1) Electrical and/or fuel gas requirements of proposed equipment;	
Identify the devices used to protect duct penetrations and air transfer openings in assemblies required to be	
protected [IBC Section 716];	
<ul> <li>Smoke control system details (where required) [IBC Section 909 and IMC Chapter 5];</li> <li>Commercial hood and duct system details (where applicable) [IBC Section 904 and IMC Chapter 5]. (See also</li> </ul>	
checklist available on our website at <a href="https://www.dps.state.la.us/sfm">www.dps.state.la.us/sfm</a> )	
PLUMBING INFORMATION	
Plans should indicate as a minimum: Fixture types and locations;	
Usable Floor Space (LSPC 407.1.3);	
Water supply and distribution, Specify source of water supply;	
<ul> <li>Identify piping materials, fittings, and valves;</li> <li>Backflow protection of potable water;</li> <li>Sanitary drainage and cleanouts;</li> <li>Specify method of sewage disposal;</li> <li>Grease trap/interceptor type, size and location (where applicable);</li> <li>Vent sizes and locations;</li> <li>Plumbing riser and dimensioned Plumbing Layout Diagram(s);</li> <li>Storm/Roof Drainage;</li> <li>Water heating equipment size and type;</li> </ul>	
Sanitary drainage and cleanouts;	
Specify method of sewage disposal;	
Grease trap/interceptor type, size and location (where applicable); Vent sizes and locations;	
Plumbing riser and dimensioned Plumbing Layout Diagram(s);	
Storm/Roof Drainage;	
<ul><li>Water heating equipment size and type;</li><li>Non-conventional plumbing designs (LSPC 1202.1 / Appendix L of LSPC, if applicable);</li></ul>	
Identify the materials and methods of construction used to protect through penetrations and membrane penetration of horizontal assemblies and fire-resistance-rated wall assemblies [IBC Section 712]	S
In accordance with the Public Health-Sanitary Code, (LAC Title 51), Part I, Section 119, certain activities require submiss	ion
of plans to the state health officer, who must approve the plans and issue a permit prior to the initiation of the activity. Re	
to the chart below to determine if submission to the DHH - Office of Public Health is required.	

to the chart below to determine if submission to the DHH - Office of Public Health is required.

Plans for proposed construction, renovation, or use of the following buildings and establishments shall be submitted to the

Plans for proposed construction, renovation, or use of the following buildings and establishments shall be submitted to the state health officer for review and approval before construction. (LAC Title 51 Part 1, Section 119)

Food or Drug Manufacturers., Distributors, Wholesalers, or Warehouses; Food

Manufacturing, Processing, Packing and Holding of Food, Drugs and Cosmetics (Part VI)	Salvaging Operations, Bottled Drinking Water Processor/Packagers (109.B) Bakeries and Manufacturing Confectioneries (505.A.1) Soft Drink Manufacturing (1105.A) Cold Storage and Ice Plants (1303.A)
Milk, Milk Products, and Manufactured Milk Products (Part VII)	All dairies from which milk or milk products are offered for sale (301.A) All milk and milk products plants from which milk or milk products are offered for sale (501.A)
Frozen Desserts (Part VIII)	Plants for the production of frozen desserts (127.A) Depots for Mobile Frozen Dessert Units (141)
Marine and Fresh Water Animal Food Products (Part IX)	Establishments for the cleaning, shucking, picking, peeling, or packing of any marine or fresh-water animal food product (313.A)
Game Bird and Small Animal Slaughter and Processing (Part X)	Every slaughter house and meat packing plant (113.B)
Animals and Animal Diseases; Rendering of Animals (Part XI)	Rendering plant (301.B)
Water Supplies (Part XII)	Public water systems/supplies (105.B)
Sewage Disposal (Part XIII)	Community sewerage system, or make a modification of an existing system which changes the system's capacity, effluent quality, point of discharge, hydraulic or contaminant loadings, or operation of the component units of the system (501.A) Individual sewerage system of any kind (701.A)
Travel Trailers and Mobile/Manufactured Homes (Part XIV – Appendices B & C)	Travel trailer parks (LSPC – B104) Mobile/Manufactured home parks (LSPC – C104)
Hotels, Lodging Houses, Boarding Houses (Part XV)	Hotel, lodging house or boarding house (105.A)
Campsites (Part XVI)	Campsite (301.A)
Public Buildings, Schools, and Other Institutions (Part XVII)	Facilities for any state agency, or any institutional buildings. Institutions include, but are not limited to schools, kindergartens, nursery schools, trade schools, colleges, universities, hospitals, nursing homes, jails, and mortuaries. (103.A)
Jails, Prisons and Other Institutions of Detention or Incarceration (Part XVIII)	Jails, prisons or other institutions of detention or incarceration (101.A)
Hospitals, Ambulatory Surgical Centers, Renal Dialysis Centers (Part XIX)	Hospital, ambulatory surgical center, or renal dialysis center (103.A)
Nursing Homes (Part XX)	Nursing home (103.A)
Day Care Centers and Residential Facilities (Part XXI)	Child and adult day care centers (103.A) Residential Facilities include, but are not limited to group homes, community homes, maternity homes, juvenile detention centers, emergency shelters, halfway homes and schools for the mentally retarded.
Retail Food Establishments (Part XXIII)	Food establishment or retail food store/market (307.A) Itinerant food establishments or itinerant retail food stores/markets (4131.A) Mobile Food Establishments/Depot (4509.A & 4523.B)
Swimming Pools and Natural or Semi- Artificial Swimming or Bathing Places (Part XXIV)	Swimming pool, water park or water slide public or private, including, but not limited to, those owned by clubs, private schools, apartment houses, and condominiums. (103.A.b)
Burial, Transportation, Disinterment or Other Disposition of Dead Human Bodies (Part XXVI)	Funeral establishments (105.A)

If the proposed project meets one or more of the descriptions above, contact a sanitarian or an engineer at the appropriate Department of Public Health regional office listed below to inquire where plans and specifications are to be submitted. In some cases, plans and specs will be reviewed by OPH sanitarians or engineers who are housed at offices other than those listed below.

1	2	3
Metro Region I	Capitol Region II	Teche Region III
1010 Common St., Suite 700	7173A Florida Blvd	1434 Tiger Dr
New Orleans, LA 70112	Baton Rouge, LA 70806	Thibodaux, LA 70301
(504) 599-0101	(225) 925-7230	(985) 449-5007 x 345
fax (504) 599-0200	fax (225) 925-3832	fax (985) 449-5011
4	5	6
Acadian Region IV	Southwest Region V	Central Region VI
825 Kaliste Saloom	707 A East Prien Lake Road	5604-B Coliseum Blvd
Bldg. 3, Suite 100	Lake Charles, LA 70601	Alexandria, LA 71303
Lafayette, LA 70508	(337) 475-3200	(318) 487-5262
(337) 262-5311	fax (337) 475-3222	fax (318) 487-5338
fax (337) 262-5638		
7	8	9
Northwest Region VII	Northeast Region VIII	Southeast Region IX
1525 Fairfield Ave, Room 566	1650 Desiard Street 2nd Floor	21454 Koop Dr., Suite 1C
Shreveport, LA 71101	Monroe, LA 71201	Mandeville, LA 70471
(318) 676-7470	(318) 361-7201	(985) 871-1300
fax (318) 676-5170	fax (318) 362-3163	fax (985) 871-1335

Plans should indicate as a minimum:
 Fuel Gas type;
 Pipe sizes, entrance location(s), controls;
Equipment and appliance locations;
Schedules of equipment and appliance demands;
Required clearances to combustible materials;
 Combustion, Ventilation, and Dilution air requirements, locations and details;
 Chimney and vent sizes, locations, and details;
 Identify the materials and methods of construction used to protect through penetrations and membrane penetrations
 of horizontal assemblies and fire-resistance-rated wall assemblies [IBC Section 712]

### ELECTRICAL INFORMATION Plans should indicate as a minimum:

**FUEL GAS INFORMATION** 

i lano oriodia irialoato do a riililiiriarii.
 Receptacle and Lighting locations with circuits identified and symbol legends;
 GFCI locations;
 Exit Signage and Emergency Lighting locations [IBC Sections 1006 and 1011];
 Equipment and Fixture schedules;
 Service Entrance Feeder riser diagrams;
 Indicate Meter type and location;
 Transformer Ground fault calculations;
 Panelboard ratings & locations;
Balanced panel load schedules in amps and KVA;
Size and ratings of all overcurrent protection devices;
Specify all conductor sizes in accordance with NEC 215.5, 215.2, 220.3 and annex G 80.21(a)(b)(c) requirements.
Identify the materials and methods of construction used to protect through penetrations and membrane penetrations
 of horizontal assemblies and fire-resistance-rated wall assemblies [IRC Section 712]

# SUGGESTED DRAWINGS AND SPECIFICATIONS FOR RENOVATION AND MAJOR REPAIR PROJECTS

COVER	SHEET INFORMATION
_	Indicate the classification of work [IEBC Chapter 4]  Repairs [IEBC Chapter 5];  Alteration – Level 1 [IEBC Chapter 6];  Alteration – Level 2 [IEBC Chapters 6 and 7];  Alteration – Level 3 [IEBC Chapters 6, 7, and 8];  Change of Occupancy [IEBC Chapter 9];  Additions (Refer to NEW CONSTRUCTION AND ADDITIONS above);  Historic Buildings [IEBC Section 408 and Chapter 11];  Relocated Buildings [IEBC Chapter 12].
	Identify the proposed occupancy classification(s) [IBC Chapter 3];
	Where multiple occupancy classes (not classified as "Accessory" to the main occupancy), are included, indicate whether designed as separated or nonseparated occupancies [IBC Section 508]; Identify any "Accessory Occupancies" [IBC Section 508.2]; (other occupancy types less than 10% of the area of the floor.) Indicate any "Special Detailed Requirements" [IBC Chapter 4];
	Identify the new construction type (and Existing, if different) [IBC Table 601];
	Indicate the gross square footage of the proposed work on each floor, including any covered open areas that are subject to occupancy. In addition, indicate the gross area of each floor of the existing building [IBC Section 502];
_	Document compliance with the allowable height and building area limitations [IBC Chapter 5]. Provide calculations if area modifications are used [IBC Section 506]; Identify existing and new Fire Protection Systems provided within the building [IBC Chapter 9]: IBC Chapter 16 Automatic sprinkler system type and extent; [IBC Section 903]; Alternative extinguishing systems; [IBC Section 904]; Standpipe system; [IBC Section 905]; Portable fire extinguisher size, type and locations; [IBC Section 906]; Automatic or manual fire alarm system and extent; [IBC Section 907]; Other fire protection / suppression systems provided.
	Indicate the height of the existing building [IBC Sections 502 and 504];
	Structural Design Data: Where applicable, provide the same documents as required for new construction, above. Flood Design Data: [IBC Section 1612]; If Substantial Improvement, (cost equals or exceeds 50% of market value of the structure), provide the same documents as required for new construction, above.
FI OOR	PLAN INFORMATION
	Provide floor plan(s) of the entire floor(s) where the project is located AND a floor plan of each floor level of the project drawn to a scale indicated. Plan(s) should indicate as a minimum:  Location and extent of the work of the project;  Identify the occupancy classes of any adjacent tenants in the same building;  Identify fire and smoke barriers within the building, regardless of their involvement in the project;  Room names and/or uses;  Door and Window locations;  Clearly indicate any required fire resistance rated or smoke rated construction used in the project;  Incidental Accessory Occupancies [IBC Table 508.2];  Occupancy Separations [IBC Table 508.4];  Structural protection required by the Construction Type [IBC Table 601];  Exterior walls [Table 602] including opening protection [IBC Table 705];  Corridors [IBC Section 1018 and Table 1018.1];  Shafts and Vertical Openings [IBC Section 708];  Exit Enclosures [IBC Sections 1022, 1023, and 1025];  Fire Wall separations [IBC Table 706.4];
	Fire Area Separations [IBC Table 707.3.9]; Fire Partitions [IBC Section 709];

Any other condition that may require fire or smoke resistance from requirements throughout the code;
Identify the listed tested assemblies, from an approved testing agency, used to achieve the fire resistance rating of
the proposed construction (UL, ETL, FM, GA, WP, WH, etc.) including joints in the assemblies. [IBC Section 714]; Identify key features of the Means of Egress: (Chapter 10)
Indicate occupant loads for each room in Assembly (A1, A2, A3, A4, and A5) occupancies: [IBC Table 1004.1];
Indicate stair, corridor, aisle, and doorway widths in all occupancies: [IBC Section 1005];
Identify lighting, and emergency lighting locations [IBC Section 1006], and Exit Signage locations [IBC Section 1011], Indicate locations of structural elements, including shear walls used to transfer lateral forces;
Provide sufficient detail in order to demonstrate that the structure has been designed to withstand the indicated
design loads.
DULES and DETAILS
Provide information to identify features indicated in the construction documents:
Schedules to indicate door / frame and window opening sizes configurations, types, materials, fire resistance ratings and door operating hardware;
As appropriate, where the project is located in a wind borne debris region, provide details, specifications and/or schedules to identify the method of opening protection used, and its anchorage to the building, if appropriate. [IBC
Sections 1609.1.2 and 1609.2]
Identify the interior finishes used in each room of the project:
Walls and Ceilings [IBC Table 803.5]
Floors [IBC Section 804]

### ADDITIONAL INFORMATION:

Where applicable, provide the same documents as required for new construction, above. Include structural framing plans, exterior elevations, building and wall sections, mechanical, plumbing, fuel gas, and/or electrical drawings as necessary to document the scope of the work.